

Tilt Tables, ESLF 65

ESLF 65

Double acting hydraulic, Floor montage.

Tilt Tables

EdmoLift offer a new and comprehensive tilt program with a range of tilt combinations. Assembly of the tilt unit can be mounted on the lift table platform or directly on the floor.

For installation on the platform the hydraulics are the same for the tilting device and table. Tilting devices installed directly on the floor have a base frame and integral power pack. The tilt function is used to incline the lift table and make the goods more accessible in more ergonomically designed work places.



Examples of work places are control functions for loading and offloading of goods as well as production work places. The load carrier can be a pallet, crate or container.

The tilt can be customised to suit individual needs and wishes of the customer.

Product features

- Single-operation hydraulics 45° tilt angle.
- Double-operation hydraulics 90° tilt angle.
- Torque 6.5 KNm and 13 KNm.
- Platform length 900 mm, 1300 mm, 1700 mm.
- Platform width 600 mm, 800 mm, 1000 mm.
- Slide protection 230 mm include.
- Complies with European safety standard EN 1570 - CE certified.
- 24 V DC control unit and operating device with deadman's switch.
- IP54 approved electrical system.
- Safety spacing between all moving parts.
- Overload protection.
- Adjustable trap prevention safety trip bars on all four sides of the platform.
- Maintenance-free bearing surface.
- PLC control for simple customizing to specific requirements.
- User manual in 20 different languages.

Specifications, ESLF 65

Model	ESLF 65
Art. no.	36076
Closed height	320 mm
Length	800 mm
Width	1300 mm
Tilt angle	45 °

Tilt Tables, ESLF 65

Tilt over	1300
Torque	6,5 kNm
Power	0,75 kW
Weight pack. incl.	165 kg