

## Lift Trolleys

### Specifications, CZ 203

Model	CZ 203
Art. no.	524674
Capacity	200 kg
Max. platform height	920 mm
Closed height	320 mm
Length	1150 mm
Width	650 mm
Loading area width	600 mm
Loading area length	900 mm
Weight pack. incl.	65 kg

### Accessories, CZ 203

#### Turntable circular

Recessed or integrated in the lift table top. Turntable recessed into a secondary table top, fitted to the main scissor lift platform.



#### Packaging

In a rigid and durable wooden casing, in order to allow multiple handling and a safe arrival of the goods. Our product packaging is also available in a "classified version" in compliance with ISPM 15.



### CZ 203

This model has a Footpump and are coated with a 2 component lacquer.

## Lift Trolleys

EdmoLift's TZ-series is a series of stable Swedish manufactured trolleys and work tables. The trolleys are easily manoeuvrable and have a variety of different uses. TZ models can even be customised to suit the individual needs of the customers.

These lift trolleys are used wherever there is a need for lifting, assembly, transportation or where an adjustable working height is required.

With a variety of different models, with single and double scissors, a lift capacity from 200 kilos to one metric ton and a lift range from 920 mm to 1620 mm, we can offer a wide range of lift trolleys.

The trolleys are available with a foot pump or battery-driven, with an integrated battery and charger. Large, easily manoeuvred wheels with double brakes on the swivelling wheels make the trolley safe and easy to manoeuvre.

## Product features lift trolley

- Load capacity max 1000 kg.
- Easy to manoeuvre.
- B models are battery-driven with integrated charger.
- The batteries are safety assembled and are maintenance-free gel batteries.
- Lift table lengths from 900 mm to 1000 mm.
- Lift range from 920 mm to 1620 mm.
- Complies with European safety standard EN ISO 3691-5:2009 - CE certified.
- 24 V DC control unit and operating device with deadman's switch.
- Safety spacing between all moving parts.
- Overload protection.
- Variable lowering function.
- User manual in 20 different languages.