

## ALT 1500UE

External powerpack in plastic cover.

### Armlifts

Armlift's unique patented function offers an ergonomic work place with ample foot space, comfortable working positions and unrivalled accessibility. Armlift is the perfect choice for almost all work places that handle goods and components on pallets, in baskets or containers.

Loads are lifted with parallel arms that can also tilt the load in a single mechanism making Armlift an economical alternative to conventional tables which require separate lift and tilt mechanisms. Because the Armlift tilts down it is especially suited for use with high pallets, oversized baskets and containers.

The ALT U, UE and GB models have a U shaped lift table with a lowest point of just 8mm which means they can lift pallets, containers and trolleys direct from the floor.

With a variety of applications and models as well as a load capacity of between 750-3000 kilos, we can offer a large and flexible range.

The lift table is manufactured with ready to-use holes for the assembly of slide protection. The size of the lift table can be customized to suit the individual needs of the customer.

Improves productivity and reduces work injuries by eliminating work situations where you are forced to stretch, bend and twist. Stretching for components on a pallet or in a container is time-consuming and creates the risk of back injuries among operatives.

Armlift loaded with pallets and containers filled with parts, make life easier and safer while increasing productivity. Loaded pallets on the Armlift are lifted to the desired working height and tilted to the required working angle. As the level of the pallet changes the height and working angle can be adjusted to maintain a constant comfortable working position.

At EdmoLift you can find solutions for all your lifting problems.

### Product features

- Load capacity max 3000 kg.
- Lift table length from 565 mm to 820 mm.
- Individual adjustment of working height and angle with combined hand control unit.
- Two main types of loading with forklift trucks or pallet trolleys.
- Tilt function from +5° to -40° included as standard.
- Slide protection included in standard product.
- Complies with European safety standard EN 1570 – CE certified
- 24 V DC control unit and operating device with deadman's switch.
- IP54 approved electrical system.
- Safety spacing between all moving parts.
- Overload protection.
- Adjustable trap prevention safety trip bars on all sides of the platform.
- Table is equipped with hose burst valves and mechanical locks for servicing and maintenance.
- Maintenance-free bearing surface.
- Service locks dimensioned for maximum load.

# Armlifts, ALT 1500UE

- PLC control for easy adaptation to individual requirements.
- User manual in 20 different languages.

## Specifications, ALT 1500UE

Model	ALT 1500UE
Art. no.	34085
Capacity	1500 kg
Lift stroke	820 mm
Closed height	6 mm
Length	1380 mm
Width	1310 mm
Loading area width	850 mm
Loading area length	1200 mm
Lifting time	16 sec
Power	0,75 kW
Weight pack. incl.	390 kg

## Armlift, ALT 1500UE

### Truck handling chassis

Enables the lift table to be easily transported with a forklift or hand pallet truck.



### Packaging

In a rigid and durable wooden casing, in order to allow multiple handling and a safe arrival of the goods. Our product packaging is also available in a "classified version" in compliance with ISPM 15.

